



## DECT IP phones comparison chart

### Grandstream DP750/720 vs Gigaset C610

	<b>Grandstream - DP750/720</b> 	<b>Gigaset - C610 IP</b> 
<b>Handsets</b>	Up to 5	Up to 6
<b>SIP Accounts</b>	Up to 10	Up to 6
<b>Concurrent Calls</b>	Up to 4	Up to 2
<b>Hunting Group support</b>	Yes (Circular, Linear, Parallel, Shared line)	Yes
<b>Voice Codecs</b>	G.711μ/a-law, VAD, CNG, PLC, AJB, G.723.1, G.729A/B, G.726-32, iLBC, G.722, OPUS, G.722.2/AMR-WB (special order)	G.711, G.722, G.726, G.729AB, VAD, CNG
<b>Phonebook</b>	3000 entries	150 entries
<b>Call logs</b>	300 records	30 records
<b>LDAP Support</b>	Yes	No
<b>Security</b>	SIP/TLS, SRTP, HTTPS, AES-256, 802.1x	SIP/TLS
<b>Upgrade/Provisioning</b>	HTTP, HTTPS, TFTP, TR-069, XML	HTTP, HTTPS, TR-069, XML
<b>Languages</b>	Arabic, Chinese (Simplified, Traditional), Croatian, Czech, Danish, Dutch, English, Estonian, Finnish, French, German, Greek, Hebrew, Hungarian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Romanian, Russian, Slovenian, Spanish, Swedish, Turkish	Yes (languages not specified)
<b>LED indicators (Base)</b>	5 LED indicators: Power, Network, Register, Call, DECT	1 LED indicator: Paging
<b>Range</b>	300 meters outdoor and 50 meters indoor	300 meters outdoor and 50 meters indoor
<b>PoE support (Base)</b>	Yes (IEEE 802.3af class 1)	Yes (IEEE 802.3)
<b>LCD</b>	1.8 inch (128x160) color TFT LCD	1.8 inch (128x160) color TFT LCD
<b>Headset support</b>	Yes (3.5mm headset jack)	Yes (2.5mm headset jack)
<b>MWI LED (handset)</b>	3-color MWI LED	1-color MWI LED
<b>Keypad buttons</b>	23	25
<b>Hearing Aid Compatibility (HAC)</b>	Yes	Yes
<b>HD Audio</b>	Yes (both on handset and speakerphone)	Yes (both on handset and speakerphone)
<b>Battery Life</b>	25-hour talk time, 200-hour standby time	12-hour talk time, 180-hour standby time
<b>Charging via Micro-USB</b>	Yes	No